

## beledi XS

Article number: 70680419

### LIGHT TECHNOLOGY

LED	SMD linear
Light colour	830
Luminous flux	4800 lm
System power	35 W
Luminaire Efficiency	137 lm/W
Reflector	SoftBeam+

### LUMINAIRE

Weight	3.2 kg
Protection rating . class	IP 40 . I
Luminaire colour	silver

### OPTIONAL

Mounting Accessories



Light band with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, reflector with homogeneous light distribution pattern, lens optics made of PMMA, luminaire insert sheet steel, powder-coated, silver

driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



Distance (m)	Beam Diameter (m)	Beam Area (m²)	Beam Diameter (m)	Beam Area (m²)
1.0	0.36	0.40	0.36	0.40
2.0	0.72	1.61	0.72	1.61
3.0	1.08	3.63	1.08	3.63
4.0	1.44	6.48	1.44	6.48
5.0	1.80	10.26	1.80	10.26

Ø (m) E0(0°)(lx)

