

beledi XS

Article number: 70680421

LIGHT TECHNOLOGY

LED	SMD linear
Light colour	830
Luminous flux	6000 lm
System power	44.5 W
Luminaire Efficiency	135 lm/W
Reflector	SoftBeam+

LUMINAIRE

Weight	3.2 kg
Protection rating . class	IP 40 . I
Luminaire colour	silver

OPTIONAL


Mounting Accessories



Light band with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, reflector with homogeneous light distribution pattern, lens optics made of PMMA, luminaire insert sheet steel, powder-coated, silver

driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



Distance (m)	Beam Diameter (m)	Beam Area (m²)	Beam Diameter (m)	Beam Area (m²)
1.0 m	0.36	0.40	1.93	3.72
2.0 m	0.72	1.61	3.86	14.88
3.0 m	1.08	3.61	5.79	33.21
4.0 m	1.44	6.41	7.72	59.52
5.0 m	1.80	10.81	9.65	92.83

Ø (m) E0(0°)(lx)

