

## beledi XS

Article number: 70680515

### LIGHT TECHNOLOGY

|                      |            |
|----------------------|------------|
| LED                  | SMD linear |
| Light colour         | 840        |
| Luminous flux        | 4000 lm    |
| System power         | 28.5 W     |
| Luminaire Efficiency | 140 lm/W   |
| Reflector            | SoftBeam+  |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Weight                    | 3.2 kg    |
| Protection rating . class | IP 40 . I |
| Luminaire colour          | silver    |

### OPTIONAL

Mounting Accessories



Light band with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, reflector with homogeneous light distribution pattern, lens optics made of PMMA, luminaire insert sheet steel, powder-coated, silver

driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Ø (m) | E0(0°)(lx)       |
|-------|------------------|
| 1.0 m | 3.13 2.60 1288.0 |
| 2.0 m | 6.26 5.20 322.0  |
| 3.0 m | 9.39 7.80 143.0  |
| 4.0 m | 12.52 10.40 81.0 |
| 5.0 m | 15.65 13.00 52.0 |

