

beledi XS

Article number: 70680818

LIGHT TECHNOLOGY

| | |
|----------------------|------------|
| LED | SMD linear |
| Light colour | 840 |
| Luminous flux | 4800 lm |
| System power | 33.5 W |
| Luminaire Efficiency | 143 lm/W |
| Reflector | SoftBeam+ |

LUMINAIRE

| | |
|---------------------------|-----------|
| Weight | 3.2 kg |
| Protection rating . class | IP 40 . I |
| Luminaire colour | black |

OPTIONAL


Mounting Accessories



Light band with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, reflector with homogeneous light distribution pattern, lens optics made of PMMA, luminaire insert sheet steel, powder-coated, black

driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Ø (m) | E0(0°)(lx) |
|-------|------------------|
| 1.0 m | 3.13 2.60 1546.0 |
| 2.0 m | 6.26 5.20 386.0 |
| 3.0 m | 9.39 7.80 172.0 |
| 4.0 m | 12.52 10.40 97.0 |
| 5.0 m | 15.65 13.00 62.0 |

