

# Pendiro TX

Article number: 80860005

## LIGHT TECHNOLOGY

LED	SMD-Bord
Light colour	835
Luminous flux	6320 lm
System power	45 W
Luminaire Efficiency	140 lm/W
Reflector	Xtra WideFlood
Beam angle	90°

## LUMINAIRE

Rotation angle	+165° / -165°
Weight	3.7 kg
Protection rating . class	IP 20 . I
Luminaire colour	matt white




Suspended luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), extra wide, homogeneous light distribution pattern, TIR-lens made of PMMA, luminaire housing sheet steel, powder-coated, matt white, power supply via suspension cables

Canopy with SELV driver with adjustable system power in 8 steps (38 W to 64 W), choice by DIP-Switch, 220-240 V~ / 50-60 Hz, max. 16 Pcs. luminaires per circuit (B16A fuse), Steel sheet powder-coated

Order separately:

- 76500079 E-Set with Canopy, black
- 76500081 E-Set with Canopy, white
- 76500083 E-Set with Canopy, DALI, black
- 76500085 E-Set with Canopy, DALI, white
- 76500078 E-Set for 3-Ph Track, black
- 76500080 E-Set for 3-Ph Track, white
- 76500082 E-Set for 3-Ph Track, DALI, black
- 76500084 E-Set for 3-Ph Track, DALI, white

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



h (m)	Ø (m)	E0 (0°) (lx/klm)
1	2.63 . 2.50	382.5
2	5.26 . 5.00	96.6
3	7.89 . 7.50	42.5
4	10.52 . 10.00	23.9
5	13.15 . 12.50	15.3

