

## Intara CX

Article number: 51390004

## LIGHT TECHNOLOGY


LED COB
Light colour 927
Luminous flux 3350 lm
System power 41 W
Luminaire Efficiency 82 lm/W
Reflector OvalBasic
Beam angle 60° x 40°



Rotation angle 350°
Swivel angle +30°/-30°
Weight 0.72 kg
Protection rating . class IP20 . III
Luminaire colour black

## OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver





Recessed directional spot with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, exchangeable reflector unit in highsheen black plastic, with glass cover, luminaire head designed as heat sink diecast aluminium, black anodized, rotation angle 350°, swivel angle +30°/-30°, assembly ring die-cast aluminum, front ring and trim in plastic, plastic clamp spring for ceiling attachment, black, separate driver unit


76500037 driver unit, Fix Current,


220-240 V / 50-60 Hz, 1050 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

76500042 driver unit, DALI,

220-240 V / 50-60 Hz, 1050 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to  $2.5~{\rm KV}$  interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.





















www.baero.com 17.10.2025