BÄRO
Retail
Lighting

# Intara CX

Article number: 51410009

## LIGHT TECHNOLOGY

| | |
|---|---|
| LED | COB |
| Light colour | GoldenBread |
| Luminous flux | 2440 lm |
| System power | 34 W |
| Luminaire Efficiency | 72 lm/W |
| Reflector | Downlight |
| Beam angle | 60° |

## LUMINAIRE

| | |
|---|---|
| Weight | 0.67 kg |
| Protection rating . class | IP20 . III |
| Luminaire colour | black |

## OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed downlight with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with homogeneous light distribution pattern, diffuser lens, translucent, darklight reflector, aluminium, metallised, highgloss, luminaire head die-cast aluminium, powder-coated, mounting ring die-cast aluminum, front ring and coverblind plastic, black, separate driver unit

76500076 driver unit, Fix Current,
220-240 V / 50-60 Hz, 850 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500077 driver unit, DALI,
220-240 V / 50-60 Hz, 850 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.