

Intara RC 625

Article number: 50280004

LIGHT TECHNOLOGY


LED	SMD Line
Light colour	927
Luminous flux	2200 lm
System power	33 W
Luminaire Efficiency	67 lm/W
Reflector	WallWash
Beam angle	1 x 20°

LUMINAIRE

Weight	0.9kg without driver
Protection rating . class	IP 20 . III
Luminaire colour	black

OPTIONAL

Mounting Accessories
DALI driver on request



recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, color rendering index CRI > 90, chromaticity point tolerance 3 SDCM (initial), Reflector with asymmetrical light distribution pattern, 99.99% pure aluminium reflector made of MIRO-SILVER®, aluminium luminaire housing and frame, anodized, separate driver unit.

If ceilings with thickness of more than 20mm are fitted the ceiling cutout will differ. Please pay attention to the dimension in the drawing.

76500032 driver unit, fix current
220-240 V / 50-60 Hz, 900 mA, with GST18/3-pin connector, incl. 3-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 52 Stk. / B16 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

