

# Intara RD 164

Article number: 50650014

## LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 835      |
| Luminous flux        | 3050 lm  |
| System power         | 23W      |
| Luminaire Efficiency | 133 lm/W |
| Reflector            | Medium   |
| Beam angle           | 20°      |

## LUMINAIRE

|                           |                      |
|---------------------------|----------------------|
| Swivel angle              | +30° / -30°          |
| Weight                    | 0.9kg without driver |
| Protection rating . class | IP 20 . III          |
| Luminaire colour          | white                |

## OPTIONAL

RAL colours




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, 99,99% pure aluminium, segmented and faceted, cardanic, incl. glass cover, sheet metal powder coated, separate driver unit

76500034 driver unit, fix current  
220-240 V / 50-60 Hz, 600 mA, with GST18/3-pin connector, incl. 3-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500039 driver unit, DALI  
220-240 V / 50-60 Hz, 600 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |            |
|-------|------|------------|
| 1.0 m | 0.38 | 13258.0    |
| 2.0 m | 0.76 | 3315.0     |
| 3.0 m | 1.14 | 1474.0     |
| 4.0 m | 1.52 | 829.0      |
| 5.0 m | 1.90 | 531.0      |
| Ø (m) |      | E0(0°)(lx) |

