

Intara RD 164

Article number: 50650020

LIGHT TECHNOLOGY

| | |
|----------------------|----------|
| LED | COB |
| Light colour | 835 |
| Luminous flux | 5060 lm |
| System power | 41 W |
| Luminaire Efficiency | 123 lm/W |
| Reflector | Flood |
| Beam angle | 30° |

LUMINAIRE

| | |
|---------------------------|----------------------|
| Swivel angle | +30° / -30° |
| Weight | 0.9kg without driver |
| Protection rating . class | IP 20 . III |
| Luminaire colour | black |

OPTIONAL

RAL colours




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), axially symmetrical reflector with circular light distribution pattern, 99,99% pure aluminium, segmented and faceted, cardanic, incl. glass cover, sheet metal powder coated, separate driver unit

76500037 driver unit, fix current
220-240 V / 50-60 Hz, 1050 mA, with GST18/3-pin connector, incl. 3-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

76500042 driver unit, DALI
220-240 V / 50-60 Hz, 1050 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, up to 2.5 KV interference resistance, SELV, max. 52 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|-------------|
| 1.0 m | 0.48 | 12912.4 |
| 2.0 m | 0.96 | 3228.1 |
| 3.0 m | 1.44 | 1434.7 |
| 4.0 m | 1.92 | 807.0 |
| 5.0 m | 2.40 | 516.5 |
| Ø (m) | | E0(0°) [lx] |

