

## Intara RD 165

Article number: 51010115

### LIGHT TECHNOLOGY

|                      |             |
|----------------------|-------------|
| LED                  | COB         |
| Light colour         | GoldenBread |
| Luminous flux        | 2870 lm     |
| System power         | 28 W        |
| Luminaire Efficiency | 103 lm/W    |
| Reflector            | OvalBasic   |
| Beam angle           | 60° x 30°   |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Swivel angle              | 2 x 25°     |
| Weight                    | 0.9 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | stratowhite |

### OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, swivel angle +25°/-25°, luminaire housing sheet steel, powder-coated, stratowhite, separate driver unit

76500035 driver unit, Fix Current, 220-240 V / 50-60 Hz, 700 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Distance (m) | Beam Diameter (m) | Illuminance (lx) | Flux (lm) |
|--------------|-------------------|------------------|-----------|
| 1.0          | 1.05              | 0.41             | 4470.0    |
| 2.0          | 2.10              | 0.82             | 1118.0    |
| 3.0          | 3.15              | 1.23             | 497.0     |
| 4.0          | 4.20              | 1.64             | 280.0     |
| 5.0          | 5.25              | 2.05             | 179.0     |

Ø (m) E0(0°)(lx)

