BÄRO
Retail
Lighting

# Intara RD 190

Article number: 51030112

## LIGHT TECHNOLOGY

| | |
|---|---|
| LED | COB |
| Light colour | SpecialMeat |
| Luminous flux | 1640 lm |
| System power | 28 W |
| Luminaire Efficiency | 60 lm/W |
| Reflector | Flood |
| Beam angle | 40° |

## LUMINAIRE

| | |
|---|---|
| Rotation angle | 170° |
| Swivel angle | 2 x 30° |
| Weight | 1.0 kg |
| Protection rating . class | IP 20 . III |
| Luminaire colour | stratowhite |

## OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 170°, swivel angle +30°/-30°, luminaire housing sheet steel, powder-coated, stratowhite, separate driver unit

76500035 driver unit, Fix Current,
220-240 V / 50-60 Hz, 700 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.