

Intara RD 190

Article number: 51290007

LIGHT TECHNOLOGY


| | |
|----------------------|----------|
| LED | COB |
| Light colour | 840 |
| Luminous flux | 6960 lm |
| System power | 59 W |
| Luminaire Efficiency | 117 lm/W |
| Reflector | BatWing |
| Beam angle | 2 x 25° |

LUMINAIRE

| | |
|---------------------------|--------------|
| Rotation angle | 170° |
| Swivel angle | 2 x 30° |
| Weight | 1.2 kg |
| Protection rating . class | IP 20 . III |
| Luminaire colour | stratosilver |

OPTIONAL

RAL colours
Mounting Accessories
DALI Driver Unit



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), reflector with double asymmetrical light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 170°, swivel angle +30°/-30°, luminaire housing sheet steel, powder-coated, stratosilver, separate driver unit

76500010 driver unit, DALI,
220-240 V / 50-60 Hz, 1050 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

76500052 driver unit, Fix Current,
220-240 V / 50-60 Hz, 1050 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 18 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

