

## Intara SQ 174

Article number: 50660008

### LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 835      |
| Luminous flux        | 3740 lm  |
| System power         | 34 W     |
| Luminaire Efficiency | 112 lm/W |
| Reflector            | Spot     |
| Beam angle           | 16°      |

### LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Swivel angle              | +30° / -30°  |
| Weight                    | 1.1 kg       |
| Protection rating . class | IP 20 . III  |
| Luminaire colour          | stratosilver |

### OPTIONAL

RAL colours




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, cardanic, swivel angle +30°/-30°, luminaire housing sheet steel, powder-coated, stratosilver, separate driver unit

76500076 driver unit, fix current  
220-240 V / 50-60 Hz, 850 mA, with GST18/3-pin connector, incl. 3-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500077 driver unit, DALI  
220-240 V / 50-60 Hz, 850 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.29 | 24286.9     |
| 2.0 m | 0.58 | 6071.7      |
| 3.0 m | 0.87 | 2698.5      |
| 4.0 m | 1.16 | 1517.9      |
| 5.0 m | 1.45 | 971.5       |
| Ø (m) |      | E0(0°) [lx] |

