

## Intara SQ 175

Article number: 51070104

### LIGHT TECHNOLOGY

|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | PearlWhite |
| Luminous flux        | 2620 lm    |
| System power         | 23 W       |
| Luminaire Efficiency | 112 lm/W   |
| Reflector            | OvalBasic  |
| Beam angle           | 60° x 30°  |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Swivel angle              | 30°         |
| Weight                    | 1.9 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | stratoblack |

### OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle 30°, luminaire housing sheet steel, powder-coated, stratoblack, separate driver unit

76500034 driver unit, Fix Current, 220-240 V / 50-60 Hz, 600 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500039 driver unit, DALI, 220-240 V / 50-60 Hz, 600 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |             |        |
|-------|-------------|--------|
| 1.0 m | 1.05 0.41   | 4079.8 |
| 2.0 m | 2.10 0.82   | 1019.9 |
| 3.0 m | 3.15 1.22   | 453.3  |
| 4.0 m | 4.20 1.63   | 255.0  |
| 5.0 m | 5.25 2.04   | 163.2  |
| Ø (m) | E0(0°) [lx] |        |

