

Intara SQ 175

Article number: 51150111

LIGHT TECHNOLOGY

| | |
|----------------------|--------------|
| LED | COB |
| Light colour | Fish-Seafood |
| Luminous flux | 3240 lm |
| System power | 47 W |
| Luminaire Efficiency | 69 lm/W |
| Reflector | Flood |
| Beam angle | 40° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Swivel angle | 30° |
| Weight | 1.9 kg |
| Protection rating . class | IP 20 . III |
| Luminaire colour | stratowhite |

OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle 30°, luminaire housing sheet steel, powder-coated, stratowhite, separate driver unit

76500092 driver unit, Fix Current, 220-240 V / 50-60 Hz, 1200 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

76500093 driver unit, DALI, 220-240 V / 50-60 Hz, 1200 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 30 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|-------|------------|
| 1.0 m | 0.77 | 7081.0 |
| 2.0 m | 1.54 | 1771.0 |
| 3.0 m | 2.31 | 787.0 |
| 4.0 m | 3.08 | 443.0 |
| 5.0 m | 3.85 | 284.0 |
| | Ø (m) | E0(0°)(lx) |

