

Intara XR

Article number: 50880055

LIGHT TECHNOLOGY

| | |
|----------------------|---------|
| LED | COB |
| Light colour | BeColor |
| Luminous flux | 2660 lm |
| System power | 34 W |
| Luminaire Efficiency | 78 lm/W |
| Reflector | Medium |
| Beam angle | 24° |

LUMINAIRE

| | |
|---------------------------|--------------|
| Swivel angle | +25° / -25° |
| Weight | 0.69 kg |
| Protection rating . class | IP 20 . II |
| Luminaire colour | stratosilver |

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle , swivel angle +25° / -25°, stratosilver,

Inclusiv fix connected driver unit
220-240 V~ / 50-60 Hz, max. 18 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

