

## Intara XR

Article number: 50890005

### LIGHT TECHNOLOGY


|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | PearlWhite |
| Luminous flux        | 1720 lm    |
| System power         | 15 W       |
| Luminaire Efficiency | 102 lm/W   |
| Reflector            | Flood      |
| Beam angle           | 40°        |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Swivel angle              | +25° / -25° |
| Weight                    | 0.69 kg     |
| Protection rating . class | IP 20 . II  |
| Luminaire colour          | stratoblack |

### OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, die-cast aluminium, powder-coated, rotation angle , swivel angle +25° / -25°, stratoblack,

Inclusiv fix connected driver unit  
220-240 V~ / 50-60 Hz, max. 36 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Distance (m) | Beam Diameter (m) | Illuminance E0(0°) (lx) |
|--------------|-------------------|-------------------------|
| 1.0          | 0.81              | 2692.2                  |
| 2.0          | 1.62              | 673.0                   |
| 3.0          | 2.43              | 299.1                   |
| 4.0          | 3.24              | 168.3                   |
| 5.0          | 4.05              | 107.7                   |

