

# Intara XR

Article number: 50900034

## LIGHT TECHNOLOGY


|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | BeColor   |
| Luminous flux        | 2020 lm   |
| System power         | 23 W      |
| Luminaire Efficiency | 88 lm/W   |
| Reflector            | OvalBasic |
| Beam angle           | 60° x 40° |

## LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Swivel angle              | +25° / -25°  |
| Weight                    | 0.69 kg      |
| Protection rating . class | IP 20 . II   |
| Luminaire colour          | stratosilver |

## OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, die-cast aluminium, powder-coated, rotation angle , swivel angle +25° / -25°, stratosilver,

Inclusiv fix connected driver unit  
220-240 V~ / 50-60 Hz, max. 18 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

