

## Ontero EC 125

Article number: 21000160

### LIGHT TECHNOLOGY

|                      |             |
|----------------------|-------------|
| LED                  | COB         |
| Light colour         | GoldenBread |
| Luminous flux        | 3420 lm     |
| System power         | 34 W        |
| Luminaire Efficiency | 101 lm/W    |
| Reflector            | Flood       |
| Beam angle           | 40°         |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Rotation angle            | 350°        |
| Swivel angle              | 210°        |
| Weight                    | 2.1 kg      |
| Protection rating . class | IP 20 . I   |
| Luminaire colour          | stratowhite |

### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 350°, swivel angle 210°, luminaire housing die-cast aluminium, powder-coated, stratowhite

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

