

Ontero EC 125

Article number: 21110146

LIGHT TECHNOLOGY


LED	COB
Light colour	Fish-Seafood
Luminous flux	2270 lm
System power	34 W
Luminaire Efficiency	68 lm/W
Reflector	Spot
Beam angle	20°

LUMINAIRE

Rotation angle	350°
Swivel angle	210°
Weight	2.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	stratoblack

OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 350°, swivel angle 210°, luminaire housing die-cast aluminium, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.31	13709.4
2.0 m	0.62	3427.4
3.0 m	0.93	1523.3
4.0 m	1.24	856.8
5.0 m	1.55	548.4
Ø (m)		E0(0°) [lx]

