

# Ontero EC 125

Article number: 21160114

## LIGHT TECHNOLOGY

|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | PearlWhite |
| Luminous flux        | 4060 lm    |
| System power         | 41 W       |
| Luminaire Efficiency | 99 lm/W    |
| Reflector            | OvalBasic  |
| Beam angle           | 60° x 40°  |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Rotation angle            | 350°        |
| Swivel angle              | 210°        |
| Weight                    | 2.1 kg      |
| Protection rating . class | IP 20 . I   |
| Luminaire colour          | stratowhite |

## OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 350°, swivel angle 210°, luminaire housing die-cast aluminium, powder-coated, stratowhite

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 20 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |             |        |
|-------|-------------|--------|
| 1.0 m | 1.05 0.41   | 6322.1 |
| 2.0 m | 2.10 0.82   | 1580.5 |
| 3.0 m | 3.15 1.22   | 702.5  |
| 4.0 m | 4.20 1.63   | 395.1  |
| 5.0 m | 5.25 2.04   | 252.9  |
| Ø (m) | E0(0°) [lx] |        |

