

# Ontero EC 125

Article number: 21170110

## LIGHT TECHNOLOGY

|                      |             |
|----------------------|-------------|
| LED                  | COB         |
| Light colour         | GoldenBread |
| Luminous flux        | 4120 lm     |
| System power         | 41 W        |
| Luminaire Efficiency | 100 lm/W    |
| Reflector            | Spot        |
| Beam angle           | 20°         |

## LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Rotation angle            | 350°         |
| Swivel angle              | 210°         |
| Weight                    | 2.1 kg       |
| Protection rating . class | IP 20 . I    |
| Luminaire colour          | stratosilver |

## OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 350°, swivel angle 210°, luminaire housing die-cast aluminium, powder-coated, stratosilver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 20 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

