

Ontero ID

Article number: 20620107

LIGHT TECHNOLOGY

| | |
|----------------------|-------------|
| LED | COB |
| Light colour | SpecialMeat |
| Luminous flux | 2100 lm |
| System power | 41 W |
| Luminaire Efficiency | 51 lm/W |
| Reflector | Spot |
| Beam angle | 20° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Rotation angle | 330° |
| Swivel angle | 90° |
| Weight | 1.3 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | stratowhite |

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, rotation angle 330°, swivel angle 90°, luminaire housing die-cast aluminium, powder-coated, stratowhite

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|-------------|
| 1.0 m | 0.34 | 12777.7 |
| 2.0 m | 0.68 | 3194.4 |
| 3.0 m | 1.02 | 1419.7 |
| 4.0 m | 1.36 | 798.6 |
| 5.0 m | 1.70 | 511.1 |
| Ø (m) | | E0(0°) [lx] |

