

## Ontero ID

Article number: 20650020

### LIGHT TECHNOLOGY

|                      |              |
|----------------------|--------------|
| LED                  | COB          |
| Light colour         | Fish-Seafood |
| Luminous flux        | 1110 lm      |
| System power         | 15 W         |
| Luminaire Efficiency | 70 lm/W      |
| Reflector            | OvalBasic    |
| Beam angle           | 60° x 40°    |

### LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Rotation angle            | 330°         |
| Swivel angle              | 90°          |
| Weight                    | 1.3 kg       |
| Protection rating . class | IP 20 . I    |
| Luminaire colour          | stratosilver |

### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, exchangeable reflector unit in high-sheen black plastic, with glass cover, rotation angle 330°, swivel angle 90°, luminaire housing die-cast aluminium, powder-coated, stratosilver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

