

Ontero RA 90

Article number: 20380009

LIGHT TECHNOLOGY

| | |
|----------------------|----------|
| LED | COB |
| Light colour | 840 |
| Luminous flux | 3120 lm |
| System power | 23 W |
| Luminaire Efficiency | 135 lm/W |
| Reflector | Spot |
| Beam angle | 15° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Rotation angle | 350° |
| Swivel angle | 135° |
| Weight | 0.9 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | stratoblack |



Surface-mounted luminaire with LED, luminaire housing and head die cast aluminium, powder-coated, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, powder-coated, rotation angle 350°, swivel angle 135°, luminaire housing/head die-cast aluminium,, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|-------|-------------|
| 1.0 m | 0.28 | 20597.5 |
| 2.0 m | 0.56 | 5149.4 |
| 3.0 m | 0.84 | 2288.6 |
| 4.0 m | 1.12 | 1287.3 |
| 5.0 m | 1.40 | 823.9 |
| | Ø (m) | E0(0°) [lx] |

