BÄRO
Retail
Lighting

# Ontero XR

Article number: 20550009

## LIGHT TECHNOLOGY

| | |
|---|---|
| LED | COB |
| Light colour | 835 |
| Luminous flux | 1880 lm |
| System power | 15 W |
| Luminaire Efficiency | 125 lm/W |
| Reflector | Flood |
| Beam angle | 40° |

## LUMINAIRE

| | |
|---|---|
| Rotation angle | 330° |
| Swivel angle | +85° / -85° |
| Weight | 0.54 kg |
| Protection rating . class | IP 20 . II |
| Luminaire colour | stratosilver |

## OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry (only luminaire head and holding arm), surface alloys on inquiry, Casambi on inquiry, blends



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 330°, swivel angle +85°/-85°, luminaire head/retention arm die-cast aluminium, powder-coated, stratosilver

In-Track-Adapter, black, inclusive driver unit, Fix Current, 220-240 V~ / 50-60 Hz, max. 30 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.