

## Ontero XR

Article number: 20760004

## LIGHT TECHNOLOGY


LED COB
Light colour 927
Luminous flux 1040 lm
System power 15 W
Luminaire Efficiency 69 lm/W
Reflector NarrowSpot
Beam angle 10°

## **LUMINAIRE**

Rotation angle 400°
Swivel angle +85°/-85°
Weight 0.8 kg
Protection rating . class IP 20 . I
Luminaire colour stratoblack

## OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry (only luminaire head and holding arm) surface alloys on inquiry, honeycomb louver, blends





Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 3 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, rotation angle 400°, swivel angle +85°/-85°, luminaire head/retention arm die-cast aluminium, powder-coated, stratoblack, power-adapter, black, inclusive fix current driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

