

Ontero XR

Article number: 20780088

LIGHT TECHNOLOGY



| | |
|----------------------|----------|
| LED | COB |
| Light colour | 835 |
| Luminous flux | 3680 lm |
| System power | 34 W |
| Luminaire Efficiency | 108 lm/W |
| Reflector | Medium |
| Beam angle | 24° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Rotation angle | 400° |
| Swivel angle | +85° / -85° |
| Weight | 0.8 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | stratoblack |


OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry (only luminaire head and holding arm) surface alloys on inquiry, honeycomb louver, blends



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, rotation angle 400°, swivel angle +85°/-85°, luminaire head/retention arm die-cast aluminium, powder-coated, stratoblack, power-adaptor, black, inclusive fix current driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|-------|-------------|
| 1.0 m | 0.44 | 14558.8 |
| 2.0 m | 0.88 | 3639.7 |
| 3.0 m | 1.32 | 1617.6 |
| 4.0 m | 1.76 | 909.9 |
| 5.0 m | 2.20 | 582.4 |
| | Ø (m) | E0(0°) [lx] |

