

## Pendiro AM 290

Article number: 81230002

### LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 830      |
| Luminous flux        | 4230 lm  |
| System power         | 34 W     |
| Luminaire Efficiency | 126 lm/W |
| Reflector            | Spot     |
| Beam angle           | 20°      |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Swivel angle              | 2 x 25°     |
| Weight                    | 3.1 kg      |
| Protection rating . class | IP 20 . I   |
| Luminaire colour          | stratoblack |

### OPTIONAL

Mounting Accessor



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle 2x25°, luminaire housing sheet steel, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

