

Pendiro AM 290

Article number: 81230126

LIGHT TECHNOLOGY

LED	COB
Light colour	Fish-Seafood
Luminous flux	2920 lm
System power	41 W
Luminaire Efficiency	71 lm/W
Reflector	Spot
Beam angle	20°

LUMINAIRE

Swivel angle	2 x 25°
Weight	3.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	stratowhite

OPTIONAL

Mounting Accessor



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle 2x25°, luminaire housing sheet steel, powder-coated, stratowhite

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.36	13823.0
2.0 m	0.72	3456.0
3.0 m	1.08	1536.0
4.0 m	1.44	864.0
5.0 m	1.80	553.0
Ø (m)		E0(0°) [lx]

