

Pendiro EC 125

Article number: 81000146

LIGHT TECHNOLOGY



| | |
|----------------------|--------------|
| LED | COB |
| Light colour | Fish-Seafood |
| Luminous flux | 2270 lm |
| System power | 34 W |
| Luminaire Efficiency | 68 lm/W |
| Reflector | Flood |
| Beam angle | 40° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Weight | 3.0 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | stratoblack |

OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|-------|------------|
| 1.0 m | 0.77 | 4663.0 |
| 2.0 m | 1.54 | 1166.0 |
| 3.0 m | 2.31 | 519.0 |
| 4.0 m | 3.08 | 292.0 |
| 5.0 m | 3.85 | 187.0 |
| | Ø (m) | E0(0°)(lx) |

