

Pendiro EC 125

Article number: 81000179

LIGHT TECHNOLOGY

LED	COB
Light colour	Sun
Luminous flux	2580 lm
System power	41 W
Luminaire Efficiency	63 lm/W
Reflector	Flood
Beam angle	40°

LUMINAIRE

Weight	3.0 kg
Protection rating . class	IP 20 . I
Luminaire colour	stratowhite

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratowhite

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.77	4818.0
2.0 m	1.54	1205.0
3.0 m	2.31	536.0
4.0 m	3.08	302.0
5.0 m	3.85	193.0
	Ø (m)	E0(0°)(lx)

