

Pendiro EC 125

Article number: 81010176

LIGHT TECHNOLOGY



LED	COB
Light colour	Sun
Luminous flux	2200 lm
System power	34 W
Luminaire Efficiency	65 lm/W
Reflector	OvalBasic
Beam angle	60° x 40°

LUMINAIRE

Weight	3.0 kg
Protection rating . class	IP 20 . I
Luminaire colour	stratowhite

OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratowhite

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	1.13 0.71	2670.0
2.0 m	2.26 1.42	668.0
3.0 m	3.39 2.13	297.0
4.0 m	4.52 2.84	167.0
5.0 m	5.65 3.55	107.0
	Ø (m)	E0(0°)(lx)

