

## Pendiro EC 125

Article number: 81010202

### LIGHT TECHNOLOGY

LED	COB
Light colour	830
Luminous flux	4970 lm
System power	41 W
Luminaire Efficiency	121 lm/W
Reflector	OvalBasic
Beam angle	60° x 40°

### LUMINAIRE

Weight	3.0 kg
Protection rating . class	IP 20 . I
Luminaire colour	stratoblack

### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	1.05 0.41	7739.1
2.0 m	2.10 0.82	1934.8
3.0 m	3.15 1.22	859.9
4.0 m	4.20 1.63	483.7
5.0 m	5.25 2.04	309.6
	Ø (m)	E0(0°) [lx]

