

Pendiro EC 125

Article number: 81020014

LIGHT TECHNOLOGY

LED	COB
Light colour	830
Luminous flux	3180 lm
System power	23 W
Luminaire Efficiency	136 lm/W
Reflector	Spot
Beam angle	20°

LUMINAIRE

Weight	3.0 kg
Protection rating . class	IP 20 . I
Luminaire colour	stratoblack

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.31	19205.3
2.0 m	0.62	4801.3
3.0 m	0.93	2133.9
4.0 m	1.24	1200.3
5.0 m	1.55	768.2
	Ø (m)	E0(0°) [lx]

