

Pendiro EC 125

Article number: 81020124

LIGHT TECHNOLOGY

| | |
|----------------------|------------|
| LED | COB |
| Light colour | PearlWhite |
| Luminous flux | 2620 lm |
| System power | 23 W |
| Luminaire Efficiency | 112 lm/W |
| Reflector | Spot |
| Beam angle | 20° |

LUMINAIRE

| | |
|---------------------------|--------------|
| Weight | 3.0 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | stratosilver |

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratosilver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|-------|-------------|
| 1.0 m | 0.31 | 15823.2 |
| 2.0 m | 0.62 | 3955.8 |
| 3.0 m | 0.93 | 1758.1 |
| 4.0 m | 1.24 | 989.0 |
| 5.0 m | 1.55 | 632.9 |
| | Ø (m) | E0(0°) [lx] |

