

## Pendiro EC 125

Article number: 81040119

### LIGHT TECHNOLOGY

|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | PearlWhite |
| Luminous flux        | 2620 lm    |
| System power         | 23 W       |
| Luminaire Efficiency | 112 lm/W   |
| Reflector            | OvalBasic  |
| Beam angle           | 60° x 40°  |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Weight                    | 3.0 kg      |
| Protection rating . class | IP 20 . I   |
| Luminaire colour          | stratoblack |

### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, canopy sheet steel, powder-coated, luminaire head die-cast aluminium, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Height (m) | Beam Diameter (m) | Beam Area (m²) | Illuminance (lx) |
|------------|-------------------|----------------|------------------|
| 1.0        | 1.05              | 0.41           | 4079.8           |
| 2.0        | 2.10              | 0.82           | 1019.9           |
| 3.0        | 3.15              | 1.22           | 453.3            |
| 4.0        | 4.20              | 1.63           | 255.0            |
| 5.0        | 5.25              | 2.04           | 163.2            |

Ø (m)      E0(0°) [lx]

