BÄRO
Retail
Lighting

# Pendiro EC 125

Article number: 81040174

## LIGHT TECHNOLOGY

| | |
|---|---|
| LED | COB |
| Light colour | Sun |
| Luminous flux | 2200 lm |
| System power | 34 W |
| Luminaire Efficiency | 65 lm/W |
| Reflector | OvalBasic |
| Beam angle | 60° x 40° |

## LUMINAIRE

| | |
|---|---|
| Weight | 3.0 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | stratoblack |

## OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, canopy sheet steel, powder-coated, luminaire head die-cast aluminium, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.