

Pendiro EC 125

Article number: 81080004

LIGHT TECHNOLOGY



| | |
|----------------------|----------|
| LED | COB |
| Light colour | 840 |
| Luminous flux | 4370 lm |
| System power | 34 W |
| Luminaire Efficiency | 131 lm/W |
| Reflector | Spot |
| Beam angle | 20° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Weight | 2.7 kg |
| Protection rating . class | IP 20 . III |
| Luminaire colour | stratoblack |

OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratoblack, separate driver unit

76500076 driver unit, Fix Current, 220-240 V / 50-60 Hz, 850 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|-------------|
| 1.0 m | 0.31 | 26392.2 |
| 2.0 m | 0.62 | 6598.0 |
| 3.0 m | 0.93 | 2932.5 |
| 4.0 m | 1.24 | 1649.5 |
| 5.0 m | 1.55 | 1055.7 |
| Ø (m) | | E0(0°) [lx] |

