

# Pendiro EC 125

Article number: 81080008

## LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 840      |
| Luminous flux        | 4370 lm  |
| System power         | 34 W     |
| Luminaire Efficiency | 131 lm/W |
| Reflector            | Spot     |
| Beam angle           | 20°      |

## LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Weight                    | 2.7 kg       |
| Protection rating . class | IP 20 . III  |
| Luminaire colour          | stratosilver |

## OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratosilver, separate driver unit

76500076 driver unit, Fix Current, 220-240 V / 50-60 Hz, 850 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.31 | 26392.2     |
| 2.0 m | 0.62 | 6598.0      |
| 3.0 m | 0.93 | 2932.5      |
| 4.0 m | 1.24 | 1649.5      |
| 5.0 m | 1.55 | 1055.7      |
| Ø (m) |      | E0(0°) [lx] |

