

Pendiro ID

Article number: 80660014

LIGHT TECHNOLOGY


| | |
|----------------------|-----------|
| LED | COB |
| Light colour | 835 |
| Luminous flux | 2910 lm |
| System power | 23 W |
| Luminaire Efficiency | 125 lm/W |
| Reflector | OvalBasic |
| Beam angle | 40° x 60° |

LUMINAIRE

| | |
|---------------------------|--------------|
| Weight | 0.7 kg |
| Protection rating . class | IP 20 . III |
| Luminaire colour | stratosilver |

OPTIONEEL

RAL-colours, NCS colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, exchangeable reflector unit in high-shine black plastic, with glass cover, luminaire housing die-cast aluminium, powder-coated, stratosilver, separate driver unit

76500053 recessed canopy,
Mounting plate with accessories for recessed fitting, Connecting cable with plug
connection for driver unit (order separately), cover sheet steel, powder-coated, stratosilver


76500034 driver unit, Fix Current,
220-240 V / 50-60 Hz, 600 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500039 driver unit, DALI,
220-240 V / 50-60 Hz, 600 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

76500095 canopy with multiadapter inclusive DALI driver,
220-240 V / 50-60 Hz, 600 mA, up to 2.5 KV interference resistance, SELV, max. 95 pcs. / B16 luminaires per circuit (B16A fuse), cover sheet steel, powder-coated, stratoblack

76500096 canopy inclusive DALI driver,
220-240 V / 50-60 Hz, 600 mA, up to 2.5 KV interference resistance, SELV, max. 95 pcs. / B16 luminaires per circuit (B16A fuse), cover sheet steel, powder-coated, stratoblack

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|-----------|-------------|
| 1.0 m | 1.18 0.76 | 3284.6 |
| 2.0 m | 2.36 1.52 | 821.2 |
| 3.0 m | 3.54 2.28 | 365.0 |
| 4.0 m | 4.72 3.04 | 205.3 |
| 5.0 m | 5.90 3.80 | 131.4 |
| Ø (m) | | E0(0°) [lx] |

