

Pendiro QT

Article number: 6421000016


LIGHT TECHNOLOGY

| | |
|----------------------|----------|
| LED | COB |
| Light colour | 927 |
| Luminous flux | 2440 lm |
| System power | 23 W |
| Luminaire Efficiency | 106 lm/W |
| Reflector | Flood |
| Beam angle | 44° |

LUMINAIRE

| | |
|---------------------------|-----------|
| Protection rating . class | IP 20 . I |
| Luminaire colour | black |


OPTIONAL



Decorative suspended luminaire with integrated LED lighting head, black, incl. translucent acrylic cylinder for homogeneous illumination of the inner surface, rated lamp lifetime of the LED L80/B10 > 50000 h, colour rendering index CRI 90, chromaticity tolerance 2 SDCM (initial), reflector 99,99% high-purity aluminium in MIRO-Silver®, rotation- symmetrical reflector with circular light distribution pattern, segmented and faceted, glas cover, shade made of painted aluminium, black / traffic yellow, 28 ventilation openings (diameter 5mm) concentric circular arrangement, power feed cable and canopy in black, steel cable hanging set, ceiling-mounting, 1.5m cable, including driver

driver unit DALI, 220-240V / 50-60 Hz, SELV, up to 2.5KV interference resistance, max. 95 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|------------|
| 1.0 m | 0.81 | 4293.0 |
| 2.0 m | 1.62 | 1073.0 |
| 3.0 m | 2.43 | 477.0 |
| 4.0 m | 3.24 | 268.0 |
| 5.0 m | 4.05 | 172.0 |
| Ø (m) | | E0(0°)(lx) |

