

Pendiro QT

Article number: 6421000511


LIGHT TECHNOLOGY

| | |
|----------------------|----------|
| LED | COB |
| Light colour | 835 |
| Luminous flux | 3020 lm |
| System power | 23 W |
| Luminaire Efficiency | 131 lm/W |
| Reflector | Flood |
| Beam angle | 44° |

LUMINAIRE

| | |
|---------------------------|-----------|
| Protection rating . class | IP 20 . I |
| Luminaire colour | black |

OPTIONAL



Decorative suspended luminaire with integrated LED lighting head, black, incl. translucent acrylic cylinder for homogeneous illumination of the inner surface, rated lamp lifetime of the LED L80/B10 > 50000 h, colour rendering index CRI 80, chromaticity tolerance 2 SDCM (initial), reflector 99,99% high-purity aluminium in MIRO-Silver®, rotation- symmetrical reflector with circular light distribution pattern, segmented and faceted, glas cover, shade made of painted aluminium, black / traffic yellow, 28 ventilation openings (diameter 5mm) concentric circular arrangement, power feed cable and canopy in black, steel cable hanging set, multiadapter, 6m cable, including driver

driver unit DALI, 220-240V / 50-60 Hz, SELV, up to 2.5KV interference resistance, max. 95 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Height (m) | Beam Diameter (m) | Luminous Flux (lm) |
|------------|-------------------|--------------------|
| 1.0 m | 0.81 | 5314.0 |
| 2.0 m | 1.62 | 1328.0 |
| 3.0 m | 2.43 | 590.0 |
| 4.0 m | 3.24 | 332.0 |
| 5.0 m | 4.05 | 213.0 |

Ø (m) E0(0°)(lx)

