

# Pendiro XR

Article number: 80760004

## LIGHT TECHNOLOGY

|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | 927        |
| Luminous flux        | 1040 lm    |
| System power         | 15 W       |
| Luminaire Efficiency | 69 lm/W    |
| Reflector            | NarrowSpot |
| Beam angle           | 10°        |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Weight                    | 1.0 kg      |
| Protection rating . class | IP 20 . I   |
| Luminaire colour          | stratoblack |

## OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry (only luminaire head and holding arm, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 3 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, luminaire head die-cast aluminium, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 95 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.18 | 21120.2     |
| 2.0 m | 0.36 | 5280.0      |
| 3.0 m | 0.54 | 2346.7      |
| 4.0 m | 0.72 | 1320.0      |
| 5.0 m | 0.90 | 844.8       |
| Ø (m) |      | E0(0°) [lx] |

