

Pendiro AM 290

Article number: 81220004

LIGHT TECHNOLOGY


| | |
|----------------------|-----------|
| LED | COB |
| Light colour | 840 |
| Luminous flux | 4530 lm |
| System power | 34 W |
| Luminaire Efficiency | 133 lm/W |
| Reflector | OvalBasic |
| Beam angle | 40° x 60° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Swivel angle | 2 x 25° |
| Weight | 3.1 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | stratoblack |

OPTIONEEL


Mounting Accessor



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle 2x25°, luminaire housing sheet steel, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|-------------|--------|
| 1.0 m | 1.13 0.71 | 6047.9 |
| 2.0 m | 2.26 1.42 | 1512.0 |
| 3.0 m | 3.39 2.14 | 672.0 |
| 4.0 m | 4.52 2.85 | 378.0 |
| 5.0 m | 5.65 3.56 | 241.9 |
| Ø (m) | E0(0°) [lx] | |

