

Pendiro AM 290

Article number: 81220030

LIGHT TECHNOLOGY


LED	COB
Light colour	830
Luminous flux	5480 lm
System power	47 W
Luminaire Efficiency	115 lm/W
Reflector	OvalBasic
Beam angle	40° x 60°

LUMINAIRE

Swivel angle	2 x 25°
Weight	3.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	stratosilver

OPTIONAL


Mounting Accessor



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle 2x25°, luminaire housing sheet steel, powder-coated, stratosilver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	1.05 0.41	8533.2
2.0 m	2.10 0.82	2133.3
3.0 m	3.15 1.22	948.1
4.0 m	4.20 1.63	533.3
5.0 m	5.25 2.04	341.3
Ø (m)	E0(0°) [lx]	

