

Pendiro AM 290

Article number: 81220071

LIGHT TECHNOLOGY

LED	COB
Light colour	927
Luminous flux	3890 lm
System power	41 W
Luminaire Efficiency	95 lm/W
Reflector	OvalBasic
Beam angle	40° x 60°

LUMINAIRE

Swivel angle	2 x 25°
Weight	3.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	stratowhite

OPCJA


Mounting Accessor



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle 2x25°, luminaire housing sheet steel, powder-coated, stratowhite

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	1.05 0.41	5995.1
2.0 m	2.10 0.82	1498.8
3.0 m	3.15 1.22	666.1
4.0 m	4.20 1.63	374.7
5.0 m	5.25 2.04	239.8
Ø (m)	E0(0°) [lx]	

