

# Pendiro CP 300

Article number: 81110104

## LIGHT TECHNOLOGY

|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | PearlWhite |
| Luminous flux        | 3480 lm    |
| System power         | 34 W       |
| Luminaire Efficiency | 93 lm/W    |
| Reflector            | Spot       |
| Beam angle           | 20°        |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Swivel angle              | +25° / -25° |
| Weight                    | 3.2 kg      |
| Protection rating . class | IP 20 . I   |
| Luminaire colour          | stratoblack |

## OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire shade die-cast aluminium, powder-coated, swivel angle +25°/-25°, luminaire housing sheet steel, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse), mit 2550Ohm

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

