

Pendiro EC 125

Article number: 81020024

LIGHT TECHNOLOGY

LED	COB
Light colour	840
Luminous flux	3290 lm
System power	23 W
Luminaire Efficiency	141 lm/W
Reflector	Spot
Beam angle	20°

LUMINAIRE

Weight	3.0 kg
Protection rating . class	IP 20 . I
Luminaire colour	stratowhite

OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratowhite

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.31	19869.6
2.0 m	0.62	4967.4
3.0 m	0.93	2207.7
4.0 m	1.24	1241.9
5.0 m	1.55	794.8
Ø (m)		E0(0°) [lx]

